



Dr. Fixit Crack-X Shrinkfree

ONE TIME SHRINK-FREE FILLER FOR PLASTER CRACKS

Description

Dr. Fixit Crack-X Shrinkfree is composed of best quality polymer, properly selected fillers & additives. It is fast drying, flexible, very light weight, soft putty like material used for filling cracks in plastered surfaces because it is 100% shrink free.

Typical Applications

- Internal & external surface cracks on plaster up to 10 mm width.

Features and benefits

- Shrinkage - Non-shrink even after cured.
- Application - One time crack filling fulfills the requirement hence doesn't need 2nd coat.
- User friendly - One pack, very soft paste, easily applicable by fingers or putty knife.
- Saving - Saves time, labour & energy.
- Paintability - Easily paintable after one Day of application.
- Non-toxic - It is non-toxic hence user friendly.

Method of Application

1 SURFACE PREPARATION

- Surface must be free from dust, oil, grease, and loose particles, etc. Moisten the surface before applying Dr. Fixit Crack-X Shrinkfree.
- The cracks must be widened in V shape groove and SSD before filling Dr. Fixit Shrinkfree.
- For filling Dr. Fixit Crack-X Shrinkfree on the internal surfaces, existing POP or painter's putty must be removed till plaster surface is exposed.

2 APPLICATION

- Press Dr. Fixit Crack-X Shrinkfree firmly into the crack ONE TIME ONLY with a spatula or putty knife and level the surface.
- Handball application can also be used as per the convenience.
- Care must be taken to avoid formation of cavities or bubbles during application.
- Further POP or painters putty application can be taken up once it is fully dry.

3 CLEANING

- Clean tools & equipments by soap & water. Wash hands with soap & warm water.

Precautions & Limitations

- Not for cracks in POP or painter's putty.
- Not recommended to use under the rain.
- Not meant for structural cracks in concrete, slab, construction joints.
- Jet or Power washing on walls not advisable prior to application.
- During application below 10°C, drying time will be delayed.
- Container to be tightly closed after application.
- If filler compound becomes too dry, add potable water in ratio of 1 teaspoon in 250 ml of Dr. Fixit Crack-X Shrinkfree.



Technical Information

PROPERTIES	RESULTS
Appearance	White paste
Base	Acrylic with specially added fillers
Full curing time@ 30°C, days	7
Specific gravity	0.26 +/-0.02

Coverage: 30-35 running meters/ltr at 5 mm depth.

Packaging

350 ml & 750 ml

Shelf Life

24 months from the date of manufacturing. Store in cool & dry place, away from sun light.

Health & Safety

- As with all chemical products, caution should always be exercised.
- Protective clothing, such as gloves and goggles, should be worn (see Packing for specific instructions).
- Treat any contact to the skin or eyes with fresh water immediately.
- Should any of the products be accidentally swallowed, do not induce vomiting but call for medical assistance immediately.
- Ensure the container is available for the medical attendant to examine any relevant instructions and contents details. Reseal all containers after use and ensure product is stored as instructed on the safety section of the labelling.

Other Products Categories available

Dr. Fixit brings you the widest range of Construction Chemicals



Pidilite Industries Limited
Construction Chemicals Division
Ramkrishna Mandir Road, Post Box No. 17411
Andheri (E) Mumbai 400059 INDIA
Tel +91-22-2835 7000 • Fax +91-22-2835 7008
www.drfixit.co.in • info@drfixit.co.in

Dr. Fixit Advice Centre (Toll Free No.) 1800 209 5504

DISCLAIMER The product information & application details given by the company & its agents has been provided in good faith & meant to serve only as a general guideline during usage. Users are advised to carry out tests & take trials to ensure on the suitability of products meeting their requirement prior to full scale usage of our products. Since the correct identification of the problems, quality of other materials used and the on-site workmanship are factors beyond our control, there are no expressed or implied guarantee / warranty as to the results obtained. The company does not assume any liability or consequential damage for unsatisfactory results, arising from the use of our products.